



ISO 9001:2000 Certified

LPS Industries, General Packaging Division

Hazardous Materials Packaging

One Gallon Or One Quart Paint Can Shipper For Single, 2 Pack Or 4 Pack

Closure Instructions

1. SEAL PAINT CANS:

FOR GROUND SHIPMENTS ONLY, ATTACH 6 CAN CLIPS.
FOR AIR OR GROUND SHIPMENTS, SEAL WITH LOCKING RING.
(LOCKING RING REQUIRED FOR AIR SHIPMENTS)

2. IF SHIPPING 1 UNIT, SEAL 1 CAN AND ASSEMBLE SINGLE SHIPMENT CORRUGATED BOX,

IF SHIPPING 2 UNITS, SEAL 2 CANS AND ASSEMBLE 2 PACK CORRUGATED BOX,

IF SHIPPING 4 UNITS, SEAL 4 CANS AND ASSEMBLE 4 PACK CORRUGATED BOX.

3. PLACE EPS FOAM CAP INSERTS INTO BASE OF BOX.

4. PUT FILLED CAN/CANS IN EPS FOAM CAP INSERTS.

5. PLACE EPS FOAM CAP INSERTS ON TOP OF CAN/CANS.

6. TAPE BOX CLOSED WITH 3" REINFORCED GUMMED TAPE OR 2" 3M #375 CLEAR CARTON SEALING TAPE, OR EQUIVALENT.

ATTENTION:

To seal can:

Apply downward pressure to lid until seated completely into grooves on can.

Air: Apply downward pressure to locking ring until contacting top of can.

Ground: Lock clips into grooves on can in an evenly spaced pattern.

Outer flaps meet. Use center seam tape pattern 2.5" min. overlap



SINGLE KIT CONTAINS: ONE SINGLE SHIPMENT CARTON AND 2 EPS FOAM CAPS.

2 PACK KIT CONTAINS: ONE 2 PACK CARTON AND 4 EPS FOAM CAPS.

4 PACK KIT CONTAINS: ONE 4 PACK CARTON AND 8 EPS FOAM CAPS.

***LPS WILL ASSUME RESPONSIBILITY FOR PACKAGE INTEGRITY AND COMPLIANCE WITH ICAO/IATA, IMO AND UN STANDARDS, "ONLY", IF ALL PACKAGE COMPONENTS ARE ASSEMBLED AND PURCHASED AS A SINGLE INTEGRATED UNIT.